LOCATION: **ACTIVITY:** SUB ACTIVITY: **BEST PRACTICE No: COUNTRY OF ORIGIN:**

BEST PRACTICE Quarry **Production and Processing** Aggregate processing **BP1947 United Kingdom**

ARTICLE YEAR COMPANY: **COMPANY LOCATION:** COMPANY TEL:

2015 Hanson UK **Cefn Mawr Quarry** 07966 499299

TITLE

Primary crusher wobbler improvement

ARTICLE

DESCRIPTION

Inspite of previous improvements made to the wobbler system in the primary crusher at Hanson's Cefn Mawr Quarry, there were 16 wobbler stops during a six month period. These required employee intervention to clear blockages and reset the system. This was a hazardous task in a restricted workspace and resulted in more than 13 hours of lost production.

A root cause analysis, carried out by the quarry team, found that the one metre drop height from the laminator was causing large rocks to stun the wobblers dead. It was decided to remove the first wobbler from the system and replace it with a 30mm reinforced plate, set 500mm from the laminator, to reduce the impact and allow the stone to roll onto the next wobbler. This has been a very successful solution to the problem.

BENEFITS

- Significantly reduced down time and stoppages
 Reduced need for hazardous manual intervention
- · Good feed rate maintained
- · Reduced wear rate on wobblers
- Power consumption reduced by 20%
- · A safer working environment

ARTICLE IMAGES



Click image to enlarge



After